

T-21 CITRUS SCENTED CLEANER

DESCRIPTION: PICCO T-21 Citrus Scented Cleaner is an effective product for use on steel and concrete surfaces to clean and remove resins, oils, and dirt before sanding and/or blasting the surface for painting. PICCO T-21 Citrus Scented Cleaner is specifically recommended for cleaning up epoxy paint spills and overspray before it cures. PICCO T-21 Citrus Scented Cleaner is also an exceptional degreaser and should be used at full strength. Do not thin with water.

TYPICAL USES INCLUDE

Degreasing Parts
Fingerprint Removal

Surface Preparation
Removing Processing Oil

Epoxy Paint Clean Up
Tool Cleaner

TYPICAL PHYSICAL PROPERTIES:

COLOR:	Water Clear
COMPONENTS:	One
GLOSS:	N/A
MIXING RATIO (BY VOL.):	N/A
WT./GALLON:	7.68 lbs
POT LIFE:	N/A
VISCOSITY AT 77° F:	Water Thin
SHELF LIFE:	2 Years
SOLIDS BY WEIGHT:	0 %
SOLIDS BY VOLUME:	0 %
TEMP. RESISTANCE:	N/A
CHEM. RESISTANCE:	N/A
THEORETICAL COVERAGE:	N/A
FLASH POINT:	94° F, TCC
V.O.C.:	7.68 lbs/gal

RECOMMENDED D.F.T.: N/A

DRY TIME: @ 77° F, 55% R.H.

To Touch: N/A
To Handle: N/A
To Recoat: N/A

THINNING: Brush: N/A
Spray: N/A

APPLICATION METHODS:
Wipe, Brush, Spray, Power Washer,
Pump-Up Sprayer

FILM THICKNESS:

Wet: N/A
Dry: N/A

APPLICATION EQUIPMENT:
Pump-Up Sprayer, Power Washer,
Scrub Brush, Rags

CLEANING OF EQUIPMENT: Water

PACKAGING:

Base: Ones – Full Fill (1.0 gal) Fives – Full Fill (5.0 gal)

APPLICATION CONDITIONS:

Surface should be dry, above 50° F and at least 5° F above the dew point.

SURFACE PREPARATION:

Remove as much grease, oil, dirt, dust or other contaminants with rags or towels before using this product to ensure efficient use and performance.

Apply cleaner with a rag, brush, power washer, or pump-up type sprayer. A clean scrub brush may also be used to agitate the cleaner into the surface soil before removing the product. Repeat as needed to leave a clean surface. After cleaning, allow surface to dry completely before painting.

PREVIOUSLY PAINTED SURFACES:

Same as above. May soften some latex adhesives and paints.

RECOMMENDED TOP COAT:

Contact Picco Coatings for a coating system specifically recommended for your application requirements.

SAFETY INFORMATION**DOT CLASSIFICATION: PAINT UN 1263**

DANGER: Causes eye burns and skin irritation. Vapor harmful. Dried film of this paint may be harmful if eaten or chewed. Contains organic solvent. Do not get in eyes, on skin or on clothing. Wear eye protective equipment when handling. Keep away from heat, sparks, and flame. Avoid breathing vapor or mist. Wash thoroughly after handling. Wear appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application unless air monitoring demonstrates vapor/mist levels are below applicable level. Follow respirator manufacturer's directions for use. Keep container closed. Keep out of reach of children.

FIRST AID: IN CASE OF EYE CONTACT, IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. CALL A PHYSICIAN. FOR SKIN CONTACT, FLUSH WITH WATER AND WASH WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING AND LAUNDRER BEFORE REUSE. IF INHALED, REMOVE TO FRESH AIR. IF NOT BREATHING GIVE ARTIFICIAL RESPIRATION, PREFERABLY MOUTH-TO-MOUTH, AND CALL A PHYSICIAN.

NOTICE: Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or **fatal**.

FOR INDUSTRIAL USE ONLY.